

# Split Piso Teto

Modelo	Capacidade Refrig./ Aquec.(BTU/h)	Ph - V - Hz	Pot. Elét. Refrig. / Aquec. (W)	Nível int./ ext. de ruído dR (A)	Dimensões Unidade Interna/ Externa			Peso Unidade Interna/ Externa (kg)
					Larg. (mm)	Alt. (mm)	Prof. (mm)	
GST24-22L/E	24000/ -	1-220-60	2800/ -	49/59	1300/950	195/840	600/412	34/75
GST24-22R/E	24000/ 28500	1-220-60	2800/ 2800	49/69	1300/950	195/840	600/412	34/75
GST36-22L/A	36000/ -	3-220-60	4200/ -	49/62	1590/950	238/850	695/410	53/105
GST36-22R/A	36000/ 37000	3-220-60	4200/ 3800	49/62	1590/950	238/850	695/410	53/105
GST36-38L/A	36000/ -	3-380-60	4350/ -	49/62	1590/950	238/850	695/410	53/105
GST36-38R/A	36000/ 37000	3-380-60	4350/ 3900	49/62	1590/950	238/850	695/410	53/105
GST42-22L/A	42000/ -	3-220-60	5100/ -	55/64	1590/950	238/1250	695/410	42/112
GST42-22R/A	42000/ 46500	3-220-60	5100/ 5050	55/64	1590/950	238/1250	695/410	42/112
GST42-38L/A	42000/ -	3-380-60	5050/ -	55/64	1590/950	238/1250	695/410	42/112
GST60-22L/A	60000/ -	3-220-60	6650/ -	58/65	1590/950	238/1250	695/410	42/112
GST60-22R/A	60000/ 60000	3-220-60	6650/6050	58/65	1590/950	238/1250	695/410	42/125
GST60-38L/A	60000/ -	3-380-60	6650/ -	58/65	1590/950	238/1250	695/410	42/125
GST60-38R/A	60000/ 60000	3-380-60	6650/ 6050	58/65	1590/950	238/1250	695/410	42/125
GST80-22L/A	80000/ -	3-220-60	9500/ -	58/63	2300/990	330/1700	780/840	125/230
GST80-22R/A	80000/ 85000	3-220-60	10000/ 10000	58/63	2300/990	330/1700	780/840	126/230